

¿QUÉ CLORADOR NECESITA CADA INSTALACIÓN?

HOW TO CALCULATE YOUR POOL SALT WATER CHLORINATOR?

Para asegurar el correcto funcionamiento de nuestros equipos en piscinas públicas, no debemos basarnos solo en su volumen, como en la piscina privada, sino que se deben tener en cuenta otros parámetros como la cantidad de bañistas diarios y las horas de depuración. Sirva como guía la siguiente tabla (estos cálculos están realizados solo para piscina exterior).

To ensure a proper performance of our equipment in public swimming pools, we should not rely only on its volume, as in the private pool, but we must consider other parameters such as the number of daily bathers and the hours of filtration. Serve as a guide the following table (these calculations are made only for outdoor pool).

CLORADORES ADECUADOS PARA PISCINAS EXTERIORES | SUITABLE CHLORINATORS FOR OUTDOOR POOLS

BAÑISTAS AL DÍA BATHERS PER DAY	VOLUMEN DE AGUA WATER VOLUME						
	100 m³	200 m³	400 m³	500 m³	750 m³	1000 m³	1500 m³
50	SMC-M 75 SMC-M 50	SMC-M 100 SMC-M 75	SMC-M 150 SMC-M 150	SMC-M 150 SMC-M 150	SMC-H 250 SMC-H 250	SMC-H 300 SMC-H 300	SMC-H 500 SMC-H 500
100	SMC-M 100 SMC-M 75	SMC-M 150 SMC-M 100	SMC-M 150 SMC-M 100	SMC-H 250 SMC-H 180	SMC-H 300 SMC-H 250		
200	SMC-M 150 SMC-M 100	SMC-H 250 SMC-H 180	SMC-H 250 SMC-H 180	SMC-H 300 SMC-H 250	SMC-H 500 SMC-H 300	SMC-H 500 SMC-H 500	SMC-H 750 SMC-H 500
300			SMC-H 300 SMC-H 180		SMC-H 500 SMC-H 300		
400				SMC-H 500 SMC-H 250			
500						SMC-H 750 SMC-H 500	SMC-H 1000 SMC-H 500

■ Modelo recomendado para filtración 12 h.
Model recommended for 12 h filtration.

■ Modelo recomendado para filtración 24 h.
Model recommended for 24 h filtration.